



APPLICATION OF MCDM DIBR-ROUGH MABAC MODEL FOR SELECTION OF DRONE FOR USE IN NATURAL DISASTER CAUSED BY FLOOD

Tešić Z. Duško¹, Božanić I. Darko¹, Boža D. Miljković²

¹ Military Academy, University of Defense in Belgrade, Veljka Lukića Kurjaka 33, 11042 Belgrade, Serbia

e-mail: tesic.dusko@yahoo.com, dbozanic@yahoo.com

² Faculty of Education, University of Novi Sad, Podgorička 4, 25101 Sombor, Serbia

e-mail: bole@ravangrad.net

Abstract:

Natural disasters around the world have resulted in enormous casualties and economic damage. Floods, as one of the natural disasters caused by climate change and inadequate human attitude towards nature, often create major problems for countries on all continents. Although preventive action is one of the ways to prevent the occurrence of floods, we are witnessing that they continue to happen, so the elimination of the flood consequences and saving lives is given great attention. With the advancement of technology, modern means, machines and devices are increasingly used to rescue people from flooded areas, both to provide assistance to the endangered and their evacuation, as well as to monitor and reconnoiter flood-affected locations. The paper presents the application of the MCDM model DIBR-RoughMABAC in the selection of drones, based on the characteristics of drones, for use during floods, i.e. for surveying flooded areas and delivering necessary materials, food and water. Validation of the model was performed by analyzing its sensitivity to changes in weight coefficients.

Keywords: MCDM, rough MABAC, DIBR, flood, drone

1. Introduction

The unpredictability of climate change, worldwide, significantly affects the increase in the number of natural disasters, especially those of meteorological and hydrological origin. Natural disasters are phenomena that disrupt the normal course of life, resulting in casualties, causing great damage to property or causing loss of property, causing damage to infrastructure and greatly endangering the environment.

The occurrence of large floods often causes the problem of physical access to flooded areas, and for the purpose of reconnaissance of these places, finding people who need help, delivering the necessary medicines, food, water and other necessary materials, drones can be used. Drone (Unmanned Aircraft Vehicle) is a synthesis of unmanned aerial vehicle and a device necessary to control it, i.e. it is an aircraft that can fly without a human operator in it. Depending on their purpose, drones are equipped with different types of sensors and cameras, and their application in different areas indicates the importance of their existence. The basic and essential characteristics of drones are: weight, payload, endurance and range, speed, wing loading, cost, engine type and power.

This paper presents the MCDM model DIBR-RMABAC for the selection of drones for use during floods, i.e. for surveying flooded areas and delivery of necessary materials, food and water, based on the characteristics of drones, through two goals. The first goal is to use the DIBR method to obtain weight coefficients, which will clearly reflect the importance of

each of the criteria. The second goal refers to the selection of drones, using the RoughMABAC method, with successful and quality treatment of imprecisions and uncertainties.

Also, in the introduction, a literature review related to the research problem was given.

2. Description of MCDM models and methods

MCDM model DIBR-RoughMABAC consists of three phases. The appearance of the model is presented in Fig. 1.




Fig. 1. MCDM model DIBR-RoughMABAC

In the continuation of this part of the paper, a description of the DIBR method, rough numbers and RoughMABAC methods is given, as well as a literature review related to the methods.

3. Model application and results

By analyzing the available literature and taking into account the specifics of the research problem, the following criteria for the selection of drones are defined (Table 1) and their description is given:

Criteria	
K_1	Cost
K_2	Range
K_3	Load capacity
K_4	Flight speed
K_5	Maximum flight altitude
K_6	Maximum resistance to wind speed
K_7	Flight autonomy

Table 1. Criteria for drone selection

The criteria are ranked in order of importance, from the most important (K_1) to the least important (K_7) for a specific research problem and all are of the benefit type, except for criterion K_1 , which is an cost type. Following the phases and steps of the MCDM model, presented in Figure 1, the calculation of the weight coefficients of the criteria was approached using the DIBR method and the following weight coefficients of the criteria were obtained (Table 1):

Criterion	Weight coefficient of the criterion
K ₁	0.1916
K ₂	0.1841
K ₃	0.1569
K ₄	0.1391
K ₅	0.1167
K ₆	0.1121
K ₇	0.0994

Table 1. Weight coefficients of the criteria

After obtaining the weight coefficients of the criteria, a ranking of 7 alternatives, which represent 7 different models of drones available on the market, was performed, using the RoughMABAC method, based on the initial decision matrix (X):

	K ₁	K ₂	K ₃	K ₄	K ₅	K ₆	K ₇
A ₁	[1300, 1450]	[5.4, 6]	[1700, 2000]	[60.88, 68.4]	[5400, 6000]	[26, 32]	[0.5, 0.55]
A ₂	[1300, 1350]	[4.5, 5]	[425, 500]	[44.28, 54]	[3560, 4000]	[35, 41]	[0.49, 0.6]
A ₃	[1280, 1300]	[5.1, 6]	[900, 1000]	[48.6, 54]	[4100, 5000]	[48, 52]	[0.45, 0.5]
A ₄	[1250, 1420]	[5.1, 6]	[1620, 1800]	[45.05, 53]	[4500, 5000]	[10.5, 13]	[0.54, 0.6]
A ₅	[1245, 1355]	[5.4, 6]	[1275, 1500]	[45, 50]	[5340, 6000]	[25, 33]	[0.54, 0.6]
A ₆	[1300, 1580]	[14.95, 16.8]	[720, 800]	[44.28, 54]	[5340, 6000]	[39, 49]	[0.44, 0.52]
A ₇	[1350, 1491]	[5.1, 6]	[510, 600]	[64.8, 72]	[5400, 6000]	[32, 41]	[0.47, 0.53]

Applying all the steps of the method and the performed ranking (Table 2), it was concluded that alternative A₂ is the most acceptable solution, i.e. it is the best ranked alternative.

	Rank
A ₁	6
A ₂	1
A ₃	2
A ₄	3
A ₅	4
A ₆	7
A ₇	5

Table 2. Ranking of the alternatives

4. Sensitivity analysis

In such a complex process, such as decision-making, errors can occur, so the sensitivity analysis of the RoughMABAC method to changes in weight coefficients was performed, through 18 scenarios, where it was concluded that the RoughMABAC method is not significantly sensitive to changes in weight coefficients.

Also, the consistency of the method results was checked by calculating Spearman's rank correlation coefficient (the results are presented in Fig. 2), where it was concluded that the correlation coefficients in the defined scenarios tend towards ideal positive correlation and that the defined MCDM model is stable with respect to weight coefficients. Correlation of ranks was performed in relation to the initial rank, in accordance with the defined scenarios.




Fig. 2. The values of the Spearman's coefficients

5. Conclusions

In this part of the paper, concluding considerations are given in connection with the research and suggestions for further improvement of the model.

References

- [1] Degg, M, Natural disasters: recent trends and future prospects. *Geography* 77(3):198-209, 1992.
- [2] Cvetković, V, Zaštita kritične infrastrukture od posledica prirodnih katastrofa. 7. međunarodna znanstvenostručna konferencija "Dani kriznog upravljanja", 2014:1281–1295, 2014.
- [3] Tobin, GA, Montz, BE, *Natural Hazards: Explanation and Integration*, New York: The Guilford Press, 1997.
- [4] Jovanović, D, Arsić, M, Logistička operacija pomoći i spasavanja u elementarnim nepogodama. *Novi Glasnik*, 10-12/2004, 2004.
- [5] Milić A, Randelović A, Radovanović M, (2019), Use of drones in operations in the urban environment. 5 th International Scientific conference Safety and crisis management – Theory and practise Safety for the future – SecMan 2019:124-130, 2019.
- [6] Agbeyangi A, Odiete J, Olorunlomeye A, Review on UAVs used for Aerial Surveillance. *Journal of Multidisciplinary Engineering Science and Technology* 3(10):5713-5719, 2016.
- [7] Radovanović, M, Milić, A, Randjelovic, A, The possibility of using drones in the protection of the land security zone (Mogućnost upotrebe dronova u zaštiti kopnene zone bezbednosti). 15th International conference on risk and safety engineering, Kopaonik, Serbia, 2020:303-311, 2020.
- [8] Arjomandi, M, Agostino, S, Mammone, M, Nelson, M, Zhou, T, Classification of unmanned aerial vehicles. Report for Mechanical Engineering class, University of Adelaide, Adelaide, Australia, 2006.
- [9] Nur, F, Alrahaleh, A, Burch, R, Babski-Reeves, K, Marufuzzaman, M, Last mile delivery drone selection and evaluation using the interval-valued inferential fuzzy TOPSIS. *Journal of Computational Design and Engineering* 7(4):397-411, 2020.
- [10] Sohaib Khan, M, Ali Shah, SI, Javed, A, Mumtaz Qadri, N, Hussain, N, Drone selection using multi-criteria decision-making methods. 2021 International Bhurban Conference on Applied Sciences and Technologies (IBCAST), 2021:256-270, 2021.
- [11] Petkovics, I, Simon, J, Petkovics, A, Covic, Z, Selection of unmanned aerial vehicle for precision agriculture with multi-criteria decision making algorithm. 2017 IEEE 15th

- International Symposium on Intelligent Systems and Informatics (SISY), 2017:000151-000156, 2017.
- [12] Rakhade, RD, Patil, NV, Pardeshi, MR, Mhasde, CS, Optimal Choice of Agricultural Drone using MADM Methods. International Journal of Technological Innovation in Modern Engineering and Science (IJTIMES) 7(4), e-ISSN:2455-2585, 2021.
 - [13] Hamurcu, M, Eren, T, Selection of unmanned aerial vehicles by using multicriteria decision-making for defence. Journal of Mathematics 2020:4308756, 2020.
 - [14] Restas, A, Drone Applications for Supporting Disaster Management. World Journal of Engineering and Technology 3(03):316-321, 2015.
 - [15] Sehrawat, A, Choudhury, TA, Raj, G, Surveillance drone for disaster management and military security. 2017 International Conference on Computing, Communication and Automation (ICCCA), 2017:470-475, 2017.
 - [16] Lee, S, Har, D, Kum, D, Drone-assisted disaster management: Finding victims via infrared camera and lidar sensor fusion. In 2016 3rd Asia-Pacific World Congress on Computer Science and Engineering (APWC on CSE) IEEE, 2016:84-89, 2016.
 - [17] Daud, SMSM, Yusof, MYPM, Heo, CC, Khoo, LS, Singh, MKC, Mahmood, MS, Nawawi, H, Applications of drone in disaster management: A scoping review. Science & Justice 62(1):30-42, 2022.
 - [18] Hasan, KM, Newaz, SS, Ahsan, M S, Design and development of an aircraft type portable drone for surveillance and disaster management. International Journal of Intelligent Unmanned Systems 6(3):147-159, 2018.
 - [19] Mishra, B, Garg, D, Narang, P, Mishra, V, Drone-surveillance for search and rescue in natural disaster. Computer Communications 156:1-10, 2020.
 - [20] Saaty, RW, The analytic hierarchy process—what it is and how it is used. Mathematical Modelling, 9(3–5):161-176, 1987.
 - [21] Pamučar D, Stević Ž, Sremac S, A New Model for Determining Weight Coefficients of Criteria in MCDM Models: Full Consistency Method (FUCOM). Symmetry, 10(9):393, 2018.
 - [22] Žižović, M, Miljković, B, Marinković, D, Objective methods for determining criteria weight coefficients: A modification of the CRITIC method. Decision Making: Applications in Management and Engineering, 3(2):149-161, 2020.
 - [23] Žižović, M, Pamucar, D, Miljković, B, Karan, A, Multiple-criteria Evaluation Model for Medical Professionals Assigned to Temporary SARS-CoV-2 Hospitals. Decision Making: Applications in Management and Engineering, 4(1):153-173, 2021.
 - [24] Žižović M, Pamučar D, Ćirović G, Žižović MM, Miljković BD, A Model for Determining Weight Coefficients by Forming a Non-Decreasing Series at Criteria Significance Levels (NDSL). Mathematics, 8(5):745, 2020.
 - [25] Pamucar, D, Deveci, M, Gokasar, I, Işık, M, Zizivic, M, Concepts in Urban Mobility Alternatives Using Integrated DIBR Method and Fuzzy Dombi CoCoSo Model. Journal of Cleaner Production 323:129096, 2021.
 - [26] Pawlak Z, Rough sets-theoretical aspects of reasoning about data, Kluwer Academic Publishers, Dordrecht, 1991.
 - [27] Zhai, LY, Khoo, LP, Zhong, ZW, A rough set enhanced fuzzy approach to quality function deployment. The International Journal of Advanced Manufacturing Technology 37:613–624, 2008.
 - [28] Zhu, GN, Hu, J, Qi, J, Gu, CC, Peng, YH, An integrated AHP and VIKOR for design concept evaluation based on rough number. Advanced Engineering Informatics 29(3):408-418, 2015.
 - [29] Zhu, GN, Hu, J, Ren, H, A fuzzy rough number-based AHP-TOPSIS for design concept evaluation under uncertain environments. Applied Soft Computing 91:106228, 2020.
 - [30] Pamučar, D, Božanić, D, Lukovac, V, Komazec, N, Normalized weighted geometric Bonferroni mean operator of interval rough numbers – Application in INTERVAL ROUGH DEMATEL-COPRAS MODEL. Facta Universitatis, Series: Mechanical Engineering 16(2):171-191, 2018.

- [31] Pamučar, DS, Ćirović, G, Božanić, D, Application of interval valued fuzzy-rough numbers in multi-criteria decision making: the IVFRN-MAIRCA model. Yugoslav journal of operations research 29(2):221-247, 2019.
- [32] Božanić, D, Pamučar, D, Tešić, D, Selection of the location for construction, reconstruction and repair of flood defense facilities by IR-MAIRCA model application. In Proc. Fifth International Scientific-Profesional Conference Security and Crisis Management–Theory and Practice, SeCMan, 2019:300-308, 2019.
- [33] Đalić, I, Stević, Ž, Karamasa, C, Puška, A. (2020). A novel integrated fuzzy PIPRECIA – interval rough SAW model: green supplier selection. Decision Making: Applications in Management and Engineering 3(1):126-145, 2020.
- [34] Stević, Ž, Pamučar, D, Kazimieras Zavadskas, E, Ćirović, G, Prentkovskis, O, The selection of wagons for the internal transport of a logistics company: A novel approach based on rough BWM and rough SAW methods. Symmetry 9(11):264, 2017.
- [35] Roy, J, Adhikary, K, Kar, S, Pamucar, D, A rough strength relational DEMATEL model for analysing the key success factors of hospital service quality. Decision Making: Applications in Management and Engineering 1(1):121-142, 2018.
- [36] Pamučar, D, Ćirović, G, The selection of transport and handling resources in logistics centres using Multi-Attributive Border Approximation area Comparison (MABAC). Expert Systems with Applications 42:3016-3028, 2015.
- [37] Roy, J, Chatterjee, K, Bandyopadhyay, A, Kar, S, Evaluation and selection of medical tourism sites: A rough analytic hierarchy process-based multiattributive border approximation area comparison approach. Expert Systems 35:e12232, 2018.
- [38] Pamučar, D, Stević, Ž, Zavadskas, EK, Integration of interval rough AHP and interval rough MABAC methods for evaluating university web pages. Applied soft computing 67:141-163, 2018.
- [39] Jia, F, Liu, Y, Wang, X, (2019). An extended MABAC method for multi-criteria group decision making based on intuitionistic fuzzy rough numbers. Expert System Application 127:241-255, 2019.
- [40] Sharma, HK, Roy, J, Kar, S, Prentkovskis, O, Multi Criteria Evaluation Framework for Prioritizing Indian Railway Stations Using Modified Rough AHP-Mabac Method. Transport and Telecommunication Journal 19:113-127, 2018.
- [41] Chakraborty, S, Dandge, SS, Agarwal, S, Non-traditional machining processes selection and evaluation: A rough multi-attributive border approximation area comparison approach. Computers & Industrial Engineering 139:106201, 2020.
- [42] Yazdani, M, Pamucar, D, Chatterjee, P, Chakraborty, S, Development of a decision support framework for sustainable freight transport system evaluation using rough numbers. International Journal of Production Research 58(14):4325-4351, 2020.
- [43] Božanić, D, Tešić, D, Milićević, J, Selection of locations for deep draft tank crossing by applying fuzzy mabac method. ICMNEE 2017 The 1st International Conference on Management, Engineering and Environment, 2017:346-358, 2017.
- [44] Bozanic, D, Tešić, D, Milić, A, Multicriteria decision making model with Z-numbers based on FUCOM and MABAC model. Decision Making: Applications in Management and Engineering, 3(2):19-36, 2020.
- [45] Pamucar, D, Božanić, D, Randjelovic, A, Multi-criteria decision making: An example of sensitivity analysis. Serbian Journal of Management 12:1-27, 2017.
- [46] Muhammad, L J, Badi, I, Haruna, AA, Mohammed, IA, Selecting the Best Municipal Solid Waste Management Techniques in Nigeria Using Multi Criteria Decision Making Techniques. Reports in Mechanical Engineering 2(1):180-189, 2021.
- [47] Durmić, E, Stević, Ž, Chatterjee, P, Vasiljević, M, Tomašević, M, Sustainable supplier selection using combined FUCOM–Rough SAW model. Reports in Mechanical Engineering 1(1):34-43, 2020.
- [48] Eremina, G, Smolin, A, Martyshina, I, Convergence analysis and validation of a discrete element model of the human lumbar spine. Reports in Mechanical Engineering 3(1):62-70, 2022.

- [49] Pamučar, DS, Savin, LM, Višekriterijumski BWM-COPRAS model za izbor optimalnog terenskog vozila za prevoz putnika. Vojnotehnički glasnik/Military Technical Courier 68(1):28-64, 2020.
- [50] Jokić, Ž, Božanić, D, Pamučar, D, Selection of fire position of mortar units using LBWA and Fuzzy MABAC model. Operational Research in Engineering Sciences: Theory and Applications, 4(1):115-135, 2021.
- [51] Božanić, D, Jurišić, D, Erkić, D, LBWA – Z-MAIRCA model supporting decision making in the army. Operational Research in Engineering Sciences: Theory and Applications, 3(2):87-110, 2020.
- [52] Božanić, D, Randelović, A, Radovanović, M, Tešić, D, A hybrid LBWA-IR-MAIRCA multi-criteria decision-making model for determination of constructive elements of weapons. Facta Universitatis, Series: Mechanical Engineering, 18(3):399-418, 2020.
- [53] Pamučar D, Božanić D, Kurtov D, Fuzzification of the Saaty's scale and a presentation of the hybrid fuzzy AHP-TOPSIS model: an example of the selection of a Brigade Artillery Group firing position in a defensive operation. Vojnotehnički glasnik/Military Technical Courier, 64(4):966-986, 2016.
- [54] Srđević, B, Srđević, Z, Suvočarev, K, Analitički hijerarhijski proces: individualna i grupna konzistentnost donosilaca odluka. Vodoprivreda 41:13-21, 2009.